

OWNER: EL MONTE UNION HIGH SCHOOL DISTRICT  
PROJECT NAME: EL MONTE HIGH SCHOOL  
BLEACHERS

CLIENT ADDRESS: 3048 TYLER AVENUE, EL MONTE, CA, 91731

# LIGHTING FIXTURE SCHEDULE

TYPE	DESCRIPTION	FINISH	LAMP(S)	REMARKS	MANUFACTURER & NO.
A1 96	2'x4' RECESSED MOUNTED FLUORESCENT PRISMATIC ACRYLIC LENS, 277 VOLT	WHITE	(3) 32W TB	REFER TO TRAILER MANUFACTURER DRAWINGS.	DAYBRITE LIGHTING #2-DP-F-3-32-RA-01-277-EB10R-1/2
A2 64	2'x4' RECESSED MOUNTED FLUORESCENT PRISMATIC ACRYLIC LENS, 277 VOLT	WHITE	(2) 32W TB	REFER TO TRAILER MANUFACTURER DRAWINGS	DAYBRITE LIGHTING #2-DP-F-2-32-RA-01-277-EB10R-1/2
B1 96	1'x4' SURFACE MOUNTED FLUORESCENT VANDAL RESISTANT LENS, 277 VOLT	WHITE	(3) 32W TB	REFER TO TRAILER MANUFACTURER DRAWINGS	PMC LIGHTING #PVL9-D-S-3-T8-4-CP-WHT-277
B2 64	1'x4' SURFACE MOUNTED FLUORESCENT VANDAL RESISTANT LENS, 277 VOLT	WHITE	(2) 32W TB	REFER TO TRAILER MANUFACTURER DRAWINGS	PMC LIGHTING #PVL9-D-S-2-T8-4-CP-WHT-277
C 32	8 1/2"X8 1/2"X48" SURFACE MOUNTED FLUORESCENT, .125 PRISMATIC POLYCARBONATE LENS, 277 VOLT	WHITE	(1) 32W TB	REFER TO TRAILER MANUFACTURER DRAWINGS	MORLITE #CE89-4-1-T8-SB-E-AL-UNV
D 64	4 3/8"X10 15/16X48" SURFACE MOUNTED FLUORESCENT, .125 PRISMATIC ACRYLIC LENS, 277 VOLT	WHITE	(2) 32W TB	REFER TO TRAILER MANUFACTURER DRAWINGS	DAYBRITE LIGHTING #VDW-N-2-32-277-1/2-EB10R
E 64	4-FOOTER, STRIPLIGHT FLUORESCENT WITH WIRE GUARD, 277 VOLT	WHITE	(2) 32W TB	REFER TO TRAILER MANUFACTURER DRAWINGS	DAYBRITE LIGHTING #VDW-N-2-32-277-1/2-EB10R-HD1-173
F 32	8" DIAMETER, RECESSED MOUNTED FLUORESCENT SHOWER DOWNLIGHTS, 277 VOLT	WHITE	(1) 32W CFM	REFER TO TRAILER MANUFACTURER DRAWINGS	CAPRI #CFRIC 6V2632/R1-R12P
F1 36	7 1/2" DIAMETER, RECESSED MOUNTED FLUORESCENT DOWNLIGHTS, 277 VOLT	WHITE	(2) 18W CFQ	PROVIDE 90 MINUTE EMERGENCY BATTERY PACK UNIT AS REQUIRED. REFER TO TRAILER MANUFACTURER DRAWINGS.	CAPRI #CFR62H18Q/R6232
G 64	13" DIAMETER, SURFACE MOUNTED FLUORESCENT, 277 VOLT	WHITE	(2) 32W TB	PROVIDE 90 MINUTE EMERGENCY BATTERY PACK UNIT AS REQUIRED. REFER TO TRAILER MANUFACTURER DRAWINGS.	MORLITE #AR3-W-232-HF-E-W-8-E-0-W
H 5	EXIT LIGHT	WHITE	(1) 5W	REFER TO TRAILER MANUFACTURER DRAWINGS	MORLITE #WRE-N-VF-R-BA-SD-277
I 42	AISLE LIGHT, WALL RECESSED MOUNTED, 277 VOLT	NATURAL ALUMINUM PAINT	(1) 42W TRF	PROVIDE 90 MINUTE EMERGENCY BATTERY PACK UNIT AS REQUIRED. REFER TO TRAILER MANUFACTURER DRAWINGS.	GARDCO LIGHTING #942-C-32TRF-LV-277-NP
J 26	4.2"X11.65"X7" SURFACE WALL MOUNTED FLUORESCENT, 277 VOLT	SILVER	(1) 26W	REFER TO TRAILER MANUFACTURER DRAWINGS.	SPECTRUM LIGHTING INC. #WJ1CF-26-EX-FJ1-CG1-CP9-S1
K 64	HALF CYLINDER DOWNLIGHT MINI SCONCE WALL SURFACE MOUNTED FLUORESCENT 277 VOLT	NATURAL ALUMINUM PAINT	(2) 32W QF	PROVIDE 90 MINUTE EMERGENCY BATTERY PACK UNIT AS REQUIRED. REFER TO TRAILER MANUFACTURER DRAWINGS.	GARDCO LIGHTING #114EM-MT-277-NP-WG
L 750	3 1/4"X3 7/8"X10 1/4" WALL RECESSED MOUNTED FLUORESCENT, 277 VOLT	NATURAL ALUMINUM PAINT	(2) 13W DTT	REFER TO TRAILER MANUFACTURER DRAWINGS	GARDCO LIGHTING #DF12-ST-HFL-750MH-277-NP-QS
M 26	3 1/4"X3 7/8"X10 1/4" WALL RECESSED MOUNTED FLUORESCENT, 277 VOLT	NATURAL ALUMINUM PAINT	(2) 13W DTT	REFER TO TRAILER MANUFACTURER DRAWINGS.	HYDREL LIGHTING #4452-A-2/13-DTT-277-LLV-LPI-DNA
O 70	FLOOD LIGHT FOR TOWER LIGHTING, 120V	NATURAL ALUMINUM PAINT	(1) 70W MH	REFER TO TRAILER MANUFACTURER DRAWINGS	HYDREL LIGHTING #4640-70M-120-FL-JBA-LPI-DNA
P 169	POLE MOUNTED LED FLOOD LIGHT MOUNTED AT 25'	NATURAL ALUMINUM PAINT	(1) 169W	REFER TO DETAIL #3 ON SHEET E-402. REFER TO TRAILER MANUFACTURER DRAWINGS.	MCGRaw-EDISON #GLEON-AF-01-LED-E1-T3


# Fixture Schedule Notes

1. THE FIXTURE SCHEDULE INDICATES GENERAL DESCRIPTION OF LIGHTING FIXTURES AND MANUFACTURERS CATALOG NUMBERS. IT SHALL BE THE CONTRACTORS RESPONSIBILITY TO DETERMINE THE CORRECT CEILING CONFIGURATION AND PROVIDE THE FIXTURES WITH ALL NECESSARY TRIMS AND MOUNTING HARDWARE SO THAT BOTH THE CEILING SYSTEM AND THE FIXTURE CONSTRUCTION MATCHES. PROVIDE SEISMIC HANGERS AS REQUIRED.
2. IT SHALL BE CONTRACTORS RESPONSIBILITY TO VERIFY THE EXACT LOCATION OF ALL LIGHTING FIXTURES AND TYPE OF CEILING WITH ARCHITECTURAL REFLECTED CEILING PLAN PRIOR TO ANY WORK.
3. LIGHTING FIXTURES SHALL BE LED TYPE WITH DIMMABLE DRIVERS.
4. EMERGENCY LIGHTING FIXTURES SHALL PROVIDED WITH 90 MINUTES CAPABLE MINIMUM OPERATING CAPACITY BATTERY PACK
5. ALL RECESSED LIGHTING FIXTURES SHALL BE IC RATED

**DATE ISSUED:** 01-23-2017  
**PROJECT NO:** 2014-40163  
**SCALE:** NONE

**SHEET TITLE: \_\_\_\_\_**

**LIGHTING  
FIXTURE  
SCHEMATIC**



The logo for SVA Architects. It features the letters "SVA" in a bold, white, sans-serif font. The "S" and "V" are connected by a horizontal line that extends to the right, and the "A" has a vertical stroke on its right side. Below this, the word "ARCHITECTS" is written in a smaller, white, all-caps, sans-serif font.